



Heat or Cold Installation

Properties

- Knurled brass body internally threaded.
- Symmetrical design for automatic assembly.
- Pilot ends for accurate location.
- High pull-out and torque resistance.
- Fast installation.

Product Data

METRIC

THREAD SIZE	LENGTH (MM)	PRODUCT CODE	HOLE DIAMETER (MM)	MIN. HOLE DEPTH (MM)
M2.5 X 0.45	5.59	742318256	4.01 / 3.96	6.35
M3 X 0.5	4.75	742318322	4.01 / 3.96	5.50
M3 X 0.5	5.59	742320914	3.81 / 3.76	6.35
M3 X 0.5	5.59	742318314	4.01 / 3.96	6.35
M3.5 X 0.6	6.35	742318421	4.80 / 4.75	7.11
M3.5 X 0.6	7.11	742318439	4.80 / 4.75	7.87
M4 X 0.7	4.50	742318553	5.61 / 5.56	5.26
M4 X 0.7	7.11	742318538	5.61 / 5.56	7.87
M5 X 0.8	7.87	742318645	6.40 / 6.35	8.14
M6 X 1.0	9.50	742318678	8.03 / 7.98	10.29

UNC

THREAD SIZE	LENGTH (INCH)	PRODUCT CODE	HOLE DIAMETER (INCH)	MIN. HOLE DEPTH (INCH)
4-40	0.220	742311111	0.158 / 0.156	0.250
6-32	0.205	742311202	0.189 / 0.187	0.235
6-32	0.250	742311210	0.189 / 0.187	0.280
6-32	0.280	742311236	0.189 / 0.187	0.310
8-32	0.205	742311319	0.221 / 0.219	0.235
8-32	0.280	742311327	0.221 / 0.219	0.310
8-32	0.323	742311343	0.221 / 0.219	0.353
10-24	0.310	742311434	0.252 / 0.250	0.340
10-24	0.375	742311442	0.252 / 0.250	0.405
¼ - 20	0.375	742318686	0.316 / 0.314	0.405

UNF

THREAD SIZE	LENGTH (INCH)	PRODUCT CODE	HOLE DIAMETER (INCH)	MIN. HOLE DEPTH (INCH)
10-32	0.310	742312432	0.252 / 0.250	0.340
10-32	0.375	742312440	0.252 / 0.250	0.405

HOLE SIZE

The hole sizes specified are for general guidance and may require slight adjustment to suit different materials or methods of installation. The design of the hole is parallel with a maximum of 0.05mm (0.002") moulding taper. We will be pleased to quote for non-standard lengths and thread forms.